

# TR200AG-P

## Industrial Spray Gun For Heavy Materials

Our state-of-the-art **pressure-assisted cup system** combined with **special designed air cap** is the easiest way to spray high viscosity materials such as bedliner, latex, polyurethanes, gel coat, thixotropic products etc.

### High Transfer Efficiency Maximum Speed



A powerful tool for professional body shops.

### Specifications

Model	Material Feed Type						
		ø mm	bar	Nl/min	ml/min	mm	g

Industrial full size spray gun with pressure-assisted cup system							
TR200AG-13P	Gravity pressure-assisted	1.3	2.5 (36 psi)	290 (10.2cfm)	190	270	735 (with cup)
-15P		1.5			260	320	
-18P		1.8			400	380	
-20P		2.0			410	400	

Max Working Pressure: 6.8 bar (98 psi)      Cup capacity: 600ml      Temperature Range: 5 - 40 °C  
 Max Working Pressure Inside Cup: 1.5 bar (22 psi)      Air Inlet: 1/4"      Fluid Inlet: M 16 x 1.5

**CE** **Ex** **II 2 G X**  
 declaration of ATEX conformity for use in zone 1 and in zone 2

**TUBA**  
 engineering for finishing



### 100% Stainless Steel Fluid Passages

Chemical-resistant & easy to clean



### Metal Lid With Mini Pressure Regulator

Heavy duty with accurate control



### Extremely Fine Finish

High-end results for high-end needs



### Revolutionary No-rubber Design

Chemical-resistant & best-in-industry lifespan



**台州涂霸机械有限公司**  
**TAIZHOU TOOL-BAR MACHINERY CO., LTD.**  
 Yingbin Road, Songmen Town, Wenling City, Zhejiang, China, 317511  
 TAX ID: 91331081577717807W  
 Tel: +86-576-13758621668  
 www.TubaSprayGun.com | sales.tuba@gmail.com ; sales@tool-bar.cn